SOCURT INSTALLATION MANUAL

32002

Level of Difficulty

Easy

Installation difficulty levels are based on time and effort involved and may vary depending on the installer level of expertise, condition of the vehicle and proper tools and equipment.

Parts List

| Item | Qty | Description | |
|------|-----|------------------------------|--|
| 1 | 1 | Shank, 2" | |
| 2 | 1 | Grip Step [™] board | |
| 3 | 1 | Adapter plate | |
| 4 | 2 | End cap | |
| 5 | 2 | Support brace | |
| 6 | 8 | Carriage bolt, 5/16" | |
| 7 | 8 | Flat washer, 5/16" | |
| 8 | 8 | Flange nut, 5/16" | |
| 9 | 4 | Self-drilling screw | |
| | | | |

Tools Required

| - | |
|--------------|-------------------------|
| Ratchet | Drill |
| Socket, 1/2" | Phillips head drill bit |
| Wrench, 1/2" | |

* For a tools reference guide visit

curtmfg.com/trailer-hitch-installation

NOTICE

Product Photo

Visit **www.curtmfg.com** for a full-color copy of this instruction manual, as well as helpful videos, guides and much more! Before you begin installation, read all instructions thoroughly.

Proper tools will improve the quality of installation and reduce the time required.

Periodic inspection of your product should be performed to ensure all hardware and / or components remain secure.

Product Registration and Warranty

CURT stands behind our products with industry-leading warranties. To get copies of the product warranties, register your purchase or provide feedback, visit: **warranty.curtgroup.com/surveys**

Assembly

Attach the end caps (#4) to the Grip Step[™] board (#2), using the four self-drilling screws (#9).

Using four carriage bolts (#6), flat washers (#7) and flange nuts (#8), attach the adapter plate (#3) to the 2" shank (#1).

Slide the support braces (#5) into the Grip Step™ board and attach to the adapter plate using four carriage bolts, washers and nuts.



