

LD15000

MOTEUR / MOTOR	6.0HP / 4.5KW, 12 VDC
TRACTION DE LIGNE / RATED LINE PULL	15 000 LB (6804 KG)
DIMENSION TOTAL / OVERALL DIMENSIONS	555 X 196 X 249 MM
POIDS / WEIGHT	N.W.: 48 KG, G.W.: 52 KG
TÉLÉCOMMANDE / REMOTE CONTROL	12' FIL (3,7M) / 12' WIRE (3,7M)
ENGRENAGE TRAIN / GEAR TRAIN	3 NIVEAUX PLANÉTAIRES / 3 STAGE PLANETARY
ENGRENAGE RATIO / GEAR RATIO	432 : 1
EMBRAYAGE / CLUTCH	COULISSANT / SLIDING RING GEAR
DIMENSION TAMBOUR / DRUM SIZE	3,4" (89 MM) (DIA.) X 9" (228,6 MM)
ACTION FREIN / BRAKING ACTION	AUTOMATIQUE / AUTOMATIC IN-THE DRUM
CÂBLE / CABLE	10,5 MM (DIA.) X 28M (92')
ROULEAU / FAIRLEAD	4 ROULEAUX / 4-WAY ROLLER FAIRLEAD
ENTRAXE BOULON MONTAGE MOUNTING BOLT PATTERN	254 X 114,3 MM

TRACTION DE LIGNE LINE PULL (LBS/KGS)	VITESSE DE LIGNE LINE SPEED FPM (M/MIN)	MOTEUR / MOTOR (AMPS)
0	23,6FT (7.2M)	77A
3750 (1701)	10.5FT (3.2M)	152A
7500 (3402)	8.2FT (2.5M)	239A
11 250 (5102)	5.24FT (1.6M)	332A
15 000 (6804)	3.93FT (1.2M)	422A

COUCHE / LAYER	TRACTION DE LIGNE RATED LINE PULL (LBS/KGS)	CORDE TOTAL SUR TAMBOUR TOTAL ROPE ON DRUM (FT/M)
1	15 000 (6804)	19.69 (6.01)
2	12 386 (5618)	43.6 (13.3)
3	10 547 (4784)	71.8 (21.9)
4	9184 (4166)	92 (28)