

# LD17000

MOTEUR / MOTOR	6.0HP / 4.5KW, 12 VDC
TRACTION DE LIGNE / RATED LINE PULL	17 000 LBS (7727 KG)
DIMENSION TOTAL / OVERALL DIMENSIONS	555 X 196 X 249 MM
POIDS / WEIGHT	N.W.: 54 KG, G.W.: 56 KG
ENGRENAGE TRAIN / GEAR TRAIN	3 NIVEAUX PLANÉTAIRES / 3 STAGE PLANETARY
ENGRENAGE RATIO / GEAR RATIO	432 : 1
EMBRAYAGE / CLUTCH	COULISSANT / SLIDING RING GEAR
DIMENSION TAMBOUR / DRUM SIZE	3,4" (89 MM) (DIA.) X 9" (228,6 MM)
ACTION FREIN / BRAKING ACTION	AUTOMATIQUE / AUTOMATIC IN-THE DRUM
CÂBLE / CABLE	12 MM (DIA.) X 26M
ROULEAU / FAIRLEAD	4 ROULEAUX / 4-WAY ROLLER FAIRLEAD
ENTRAXE BOULON MONTAGE MOUNTING BOLT PATTERN	254 X 114,3 MM

TRACTION DE LIGNE LINE PULL (LBS/KGS)	VITESSE DE LIGNE LINE SPEED FPM (M/MIN)	MOTEUR / MOTOR (AMPS)
0	23.9FT (7.3M)	75A
7200 (3266)	8.01FT (2.44M)	206A
10 800 (4899)	5.08FT (1.55M)	308A
14 400 (6531)	4.1FT (1.25M)	384A
17 000 (7727)	3.05FT (0.93M)	501A

COUCHE / LAYER	TRACTION DE LIGNE RATED LINE PULL (LBS/KGS)	CORDE TOTAL SUR TAMBOUR TOTAL ROPE ON DRUM (FT/M)
1	17 000 (7727)	17.5 (5.33)
2	14 544 (6611)	39.2 (11.9)
3	12 201 (5546)	65.2 (19.9)
4	10 508 (4776)	85 (28)