

LDS4500A

MOTEUR / MOTOR	1.3HP, 12 VDC
TRACTION DE LIGNE / RATED LINE PULL	4500 LBS (2045 KG)
DIMENSION TOTAL / OVERALL DIMENSIONS	395 X 117 X 120 MM
ENGRENAGE RATIO / GEAR RATIO	166 : 1
DIMENSION TAMBOUR / DRUM SIZE	120 MM (LONGUEUR / LENGTH)
FREIN / BRAKING	MÉCANIQUE / MECHANICAL
CÂBLE / CABLE	5,5 MM (DIA.) X 15,2M
ENTRAXE BOULON MONTAGE MOUNTING BOLT PATTERN	76 X 168 MM

TRACTION DE LIGNE LINE PULL (LBS/KGS)	VITESSE DE LIGNE LINE SPEED FPM (M/MIN)	MOTEUR / MOTOR (AMPS)
0	24.11FT (7.35M)	26A
1125 (511)	14.27FT (4.35M)	109A
2250 (1022)	9.31FT (2.84M)	155A
3375 (1534)	6.88FT (2.1M)	196A
4500 (2045)	5.41FT (1.65M)	238A

COUCHE / LAYER	TRACTION DE LIGNE RATED LINE PULL (LBS/KGS)	CORDE TOTAL SUR TAMBOUR TOTAL ROPE ON DRUM (FT/M)
1	4500 (2041)	7.22 (2.2)
2	3700 (1678)	16.08 (4.9)
3	3200 (1451)	26.57 (8.1)
4	2800 (1270)	39.37 (12)