

LDS6000

MOTEUR / MOTOR	5.0HP / 3.75KW, 12 VDC
TRACTION DE LIGNE / RATED LINE PULL	6000 LBS (2721 KG)
DIMENSION TOTAL / OVERALL DIMENSIONS	440 X 160 X 218 MM
TÉLÉCOMMANDE / REMOTE CONTROL	12' FIL (3,7M) / 12' WIRE (3,7M)
ENGRENAGE TRAIN / GEAR TRAIN	3 NIVEAUX PLANÉTAIRES / 3 STAGE PLANETARY
ENGRENAGE RATIO / GEAR RATIO	235 : 1
EMBAYAGE / CLUTCH	COULISSANT / SLIDING RING GEAR
DIMENSION TAMBOUR / DRUM SIZE	2,52" (64 MM) (DIA.) X 5,26" (134 MM)
ACTION FREIN / BRAKING ACTION	AUTOMATIQUE / AUTOMATIC IN-THE DRUM
CÂBLE / CABLE	7,2 MM (DIA.) X 24M (79')
ROULEAU / FAIRLEAD	4 ROULEAUX / 4-WAY ROLLER FAIRLEAD

TRACTION DE LIGNE LINE PULL (LBS/KGS)	VITESSE DE LIGNE LINE SPEED FPM (M/MIN)	MOTEUR / MOTOR (AMPS)
0	10.0FT (3.1M)	30A
2000 (907)	7.5FT (2.3M)	120A
4000 (1814)	4.9FT (1.5M)	210A
6000 (2721)	2.9FT (0.9M)	320A

COUCHE / LAYER	TRACTION DE LIGNE RATED LINE PULL (LBS/KGS)	CORDE TOTAL SUR TAMBOUR TOTAL ROPE ON DRUM (FT/M)
1	6000 (2721)	13.0 (4.0)
2	4990 (2263)	29.0 (9.0)
3	4280(1941)	48.0 (14.6)
4	3730 (1692)	69.0 (21.0)
5	3310 (1501)	79.0 (24.0)